

# CS 15 2+0

Power Line SPDs  
DIN RAIL - IEC TYPE 2



## General Data

Internal configuration	2+0
No. Poles	2-Pole
No. DIN rail modules	2
Network configuration	TNS
IEC SPD Type	Class II
EN SPD Type	Type 2
Format	Monobloc
Protection Modes	L-N / N-PE
Product standards	IEC 61643-11; EN 61643-11



## PART NUMBERS

<b>XXX</b>	<b>230</b>
CS2P-15/ <b>XXX</b>	77705228
CS2P-15/ <b>XXX</b> IR (with Remote Indication)	77705229

## SURGE PROTECTION DEVICE (SPD) - IEC TECHNICAL FEATURES

CS2P-15/ <b>XXX</b> , CS2P-15/ <b>XXX</b> IR (with Remote Indication)	<b>230</b>
Maximum continuous operating voltage (AC) - U <sub>c</sub> [V]	275
Nominal voltage AC 50-60 Hz - U <sub>n</sub> [V]	230
Nominal voltage AC 50-60 Hz - U <sub>n</sub> (L-N) [V]	230
Nominal discharge current (8/20)- I <sub>n</sub> [kA]	5
Nominal discharge current (8/20) - I <sub>n</sub> (L-PE) [kA]	5
Max Discharge Current (8/20) - I <sub>max</sub> (L-PE) [kA]	15
Voltage protection level at I <sub>n</sub> - U <sub>p</sub> [kV]	≤1,2
Voltage protection level at I <sub>n</sub> - U <sub>p</sub> (L-PE) [kV]	≤1,2
Maximum back-up fuse [A [gG]]	63
Short circuit withstand- I <sub>scrr</sub> [kA]	10
Response time - t <sub>A</sub> (L-PE) [ns]	≤25

## MECHANICAL AND ENVIRONMENTAL FEATURES

CS2P-15/ <b>XXX</b> , CS2P-15/ <b>XXX</b> IR (with Remote Indication)	<b>230</b>
Temperature range [°C]	-40 ... 85
Humidity range [%]	5 ... 95
Indication System Type	LED
Insulating material	PC+GF
Housing color	Grey RAL 7035
Enclosure - IP	IP20
Flammability class	UL94 V-0
Solid conductor cross section	6...35 mm <sup>2</sup>
Stranded conductor cross section	6...25 mm <sup>2</sup>
Torque rating [N m]	4


## DATASHEET

This document is subject to change at any time without notice [www.cirprotec.com](http://www.cirprotec.com) | Lepanto 49 · 08223 Terrassa, Barcelona Spain © 2024 Cirprotec SLU | All rights reserved

**cirprotec**


# CS 15 2+0

## DIMENSIONS AND WEIGHT



CS2P-15/XXX CS2P-15/XXX IR (with Remote Indication)	<b>230</b>
Net Weight [kg]	0.132
Gross weight [kg]	0.161
Packaging dimensions (H x W x L) [mm]	117 × 42 × 90

## INTERNAL CONFIGURATION



## DATASHEET