



General Data

No. DIN rail modules	1
Format	DIN
Product standards	IEC 61643-21



PART NUMBERS

DIN-ADSL	77840115
----------	----------

SURGE PROTECTION DEVICE (SPD) - IEC TECHNICAL FEATURES

Maximum continuous operating voltage (AC) - U_c (L-PE) [V]	180
Nominal voltage AC 50-60Hz - U_n (L1/L2-PE) [V]	50
Nominal discharge current (8/20) - I_n [kA]	0.1
Nominal discharge current (8/20) - I_n (L-PE) [kA]	5
Max Discharge Current (8/20) - I_{max} (L-PE) [kA]	10
Voltage protection level at I_n - U_p (L1/L2-PE) [V]	≤ 200


TECHNICAL FEATURES

Network communication standards	ADSL
No. protected pairs	1
Bandwidth [MHz]	3
Max. communication voltage [V]	200

MECHANICAL AND ENVIRONMENTAL FEATURES

Temperature range [°C]	-40 ... 60
Insulating material	Polycarbonate
Housing color	Grey RAL 7035
Enclosure - IP	IP20
Flammability class	UL94 V-0
Input connector	Terminal
Output connector	Terminal
Stranded conductor cross section	0.5...2.5 mm ²

DIMENSIONS AND WEIGHT



Net Weight [kg]	0.049
Gross weight [kg]	0.068
Packaging dimensions (H x W x L) [mm]	117 × 24 × 90