

PSC 12,5 4+0 IT

Power Line SPDs

DIN RAIL - IEC TYPE 1+2



General Data

Internal configuration	4+0
No. Poles	4-Pole
No. DIN rail modules	4
Network configuration	IT
IEC SPD Type	Class I+II
EN SPD Type	Type 1+2
Format	Pluggable
Protection Modes	L-PE / N-PE
Product standards	IEC 61643-11; EN 61643-11



PART NUMBERS

PSC4-12,5/400 IT

77738432

SURGE PROTECTION DEVICE (SPD) - IEC TECHNICAL FEATURES

Maximum continuous operating voltage (AC) - Uc [V]	440
Nominal voltage AC 50-60 Hz - Un [V]	400/690
Nominal discharge current (8/20)- In [kA]	20
Max Discharge Current (8/20) - I _{max} [kA]	65
Lightning impulse current (10/350) - I _{imp} [kA]	12.5
Voltage protection level at In - Up [kV]	≤1,8
Short circuit withstand- I _{sc} [kA]	25
Response time - t _A [ns]	≤25
Dynamic thermal disconnection	Yes
Thermal protection behaviour	OCM (Open Circuit Mode)

MECHANICAL AND ENVIRONMENTAL FEATURES

Temperature range [°C]	-40 ... 85
Humidity range [%]	5 ... 95
Indication System Type	Green (OK) / Not green (replace)
Insulating material	PA66 CT1
Enclosure - IP	IP20
Flammability class	UL94 V-0
Solid conductor cross section	6...35 mm ²
Stranded conductor cross section	6...25 mm ²
Torque rating [N m]	3

DATASHEET


This document is subject to change at any time without notice www.cirprotec.com | Lepanto 49 · 08223 Terrassa, Barcelona Spain © 2024 Cirprotec SLU | All rights reserved

cirprotec

PSC 12,5 4+0 IT


Power Line SPDs
DIN RAIL - IEC TYPE 1+2

DIMENSIONS AND WEIGHT



Net Weight [kg]	0.63
Gross weight [kg]	0.661
Packaging dimensions (H x W x L) [mm]	117 × 78 × 90

INTERNAL CONFIGURATION



REPLACEMENT CARTRIDGES

PSC-12,5/400 (Line)	77738601
---------------------	----------

DATASHEET

This document is subject to change at any time without notice www.cirprotec.com | Lepanto 49 · 08223 Terrassa, Barcelona Spain © 2024 Cirprotec SLU | All rights reserved